

METROTECH

10-Watt Transmitter

Loc3 Series Broadband Transmitter

- Built-in AVO meter
- Optional transmitter-to-receiver radio link
- SD mode for positive location in congested areas
- Lightweight - Only 7.15 lbs. / 3.24 kg with Li-ion battery
- AC/DC external power sources

The Loc3 series 10-Watt broadband transmitter has selectable induction and direct connection frequencies from 98Hz to 200kHz, SD mode (Signal Direction), fault find and true resistance measurement up to 1 Mohm. The two inch by one inch dot matrix display with LED backlight shows output current, connection type, volts, resistance, frequency, volume, battery condition and high voltage warnings.

The optional Transmitter Link (Tx-Link) installed in the receiver and transmitter, remote operation of the transmitter from the receiver is possible. The range of the radio transmitter link depends on having a clear "line of sight" between receiver and transmitter but is typically around 985 ft. / 300m.

Signal Direction (SD) mode feature verifies if the line being located is the target that the transmitter is connected to. When a transmitter is connected to a target line, the signal travels along it and finds the easiest way to travel back, usually via the ground and ground stake. However, very often the signal will travel back along adjacent utilities which offer an easier route. As a result, there can be multiple signals radiating from utilities in the area making it difficult to identify the target line. These return signals are typically traveling in the opposite direction than the applied signal. The Signal Direction feature identifies which direction the signal is flowing and hence the target line.

Packaged in a lightweight, rugged, ergonomic IP54 housing, the transmitter provides consistent current output in direct connect, clamp or induction modes and protection against incoming voltages up to 240V.



Loc3-10Tx Transmitter Specifications													
Construction	High impact ABS injection molded housing												
Weight and Dimensions	6.2lbs (2.8kg), 13.1in(L) x 7.2in(W) x 7.3in(H) (332mm x 182mm x 185mm)												
Display	2.4in x 1.3in (60mm x 32mm Monochrome-dot-matrix graphic LCD display with LED backlight)												
Battery options	Supplied with 12 x D cell alkaline batteries Optional Li-ion rechargeable battery tray with charger												
Battery life	At 70°F (21°C) - continuous use (based on the battery type and quality) <table border="1"> <thead> <tr> <th>Output Power</th> <th>Alkaline</th> <th>Li-ion (Rechargeable)</th> </tr> </thead> <tbody> <tr> <td>1 watt</td> <td>25 hours</td> <td>50 hours</td> </tr> <tr> <td>5 watt</td> <td>6 hours</td> <td>10 hours</td> </tr> <tr> <td>10 watt</td> <td>4 hours</td> <td>6 hours</td> </tr> </tbody> </table> Li-ion batteries will withstand 500 charging life cycles	Output Power	Alkaline	Li-ion (Rechargeable)	1 watt	25 hours	50 hours	5 watt	6 hours	10 hours	10 watt	4 hours	6 hours
Output Power	Alkaline	Li-ion (Rechargeable)											
1 watt	25 hours	50 hours											
5 watt	6 hours	10 hours											
10 watt	4 hours	6 hours											
Operating Frequencies	Induction - Available frequencies between 98kHz and 200kHz Direct Connection - Available frequencies between 98kHz and 200kHz Clamp - Frequencies between 8kHz to 131kHz												
Operating modes	Induction mode - applies signal inductively using internal antenna Direct connection mode - applies signal directly to the cable by clipping one output lead to the cable, the other to an independent ground Clamp mode - applies signal using an inductive clamp (aka toroid or coupler) that is placed around the target pipe or cable												
Output Protection	Output protected against accidental momentary connection to up to 240V AC												
Environmental	IP65 and NEMA 4												

What's in the box



Popular Accessories



Transmitter Link

Rechargeable battery

DC power lead

Clamps

Live Plug connector

Live cable connector

Compatible Receivers



vLoc3-Pro



vLoc3-9800



vLoc3-ML



vLoc2 receiver series



VM-510FFL+

Local Vivax-Metrotech Distributor:



雷迪有限公司
Radiolocation Limited

11/F Long To Building,
654-656 Castle Peak Road, Hong Kong
Tel (852) 2803 5881 Fax (852) 2803 5863
www.radiolocation.com.hk



ISO 9001
FS593165



ISO 9001
FS593165

Allied Power
We Empower Your Business

奥
华

Unit B, 11/F Long To Building,
654-656 Castle Peak Road,
Lai Chi Kok, Kowloon, Hong Kong

Tel: +852 3746 9033

Fax: +852 2120 8765

Email: contact@alliedpower.com.hk

Web: www.alliedpower.com.hk



V1.1